



MADE FOR SHOOTERS. BY SHOOTERS.

GUNSHIELD™ BFG GUN OIL

Technical sheet | Manual EN

Multipurpose High-Tech Gun Oil

General introduction

BFG GUN OIL is a special blend of high-quality oils and other additives. It is designed for lubrication and maintenance of metal parts of all kinds of weapons. GUNSHIELD™ BFG GUN OIL has degreasing and cleaning properties, high capillarity and excellent penetrating capacity even in small gaps such as tight sliding parts of the gun slide, trigger mechanisms etc. Disrupts and dissolves rust. At the same time, creates an oil microfilm and a chemical anticorrosive layer which has excellent long-term lubricating properties, reducing friction of individual parts to a minimum level. The agent gets partially dry, increasing its viscosity after application, does not run off and forms a thin protective film. No disruption of surface finish and plastic parts of weapons. No silicone or Teflon.

Application methods

Multipurpose oil GUNSHIELD™ BFG GUN OIL may be applied by smearing, spraying, dipping, with a wad etc. In most cases the agent may be freely combined with operating oils, petrolatum and other preservatives.

Examples of use

Lubrication and protection of weapon systems, handguns, knives as well as tools, machinery products etc. Cleaning and lubrication of sliding and rolling components including bearings. Releasing stiff joints, especially threaded fasteners, and rust proofing. Wherever oils are used for lubrication and corrosion protection.

Benefits

Several functions in one agent. High lubricity and cleaning capability integrated with protective efficacy and corrosion disruption at very low consumption. Relatively long corrosion protection, wide limits of miscibility with preservatives. Penetrates into otherwise inaccessible areas due to its capillarity. Once partially dry, the agent stops running off and minimizes dirt trapping.

Package

Multipurpose oil GUNSHIELD™ BFG GUN OIL comes:

- in 200 l metal drums
- in 200 ml pressure spray cans
- in 50 ml PET bottles with a dropper for easier and quick application
- on customer request, in containers by mutual agreement, alternatively the products may be delivered modified according to specifications.

Shelf life

Product shelf life is at least 24 months in its original container with temperatures ranging between 5°C and 30°C with no direct sunlight. Please observe the guidelines for work with extremely flammable substances in storage.